Lovibond[®] Water Testing

Tintometer® Group



Safety Data Sheet

acc. to OSHA HCS (HazCom 2012)

Printing date 12/05/2017

1 Identification

· Product identifier

- · Trade name: COD / CSB 0-15000 mg/l
- · Catalogue number: 424438, 2420722, 420722, 2420727, 420727
- · Application of the substance / the mixture: Reagent for water analysis
- Manufacturer/Supplier: Tintometer Inc. 6456 Parkland Drive Sarasota, FL 34243 USA phone: (941) 756-6410 fax: (941) 727-9654 www.lovibond.us Made in Germany
- · Emergency telephone number: + 1 866 928 0789 (English, French, Spanish)

2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 3 H311 Toxic in contact with skin.



GHS08 Health hazard

Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Muta. 1B	H340	May cause genetic defects.
Carc. 1B	H350	May cause cancer.
Repr. 1B	H360	May damage fertility or the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
· · · · · · · · · ·		

GHS05 Corrosion

Met. Corr.1	H290	May be corrosive to metals.
Skin Corr. 1A	H314	Causes severe skin burns and eye damage.
Eye Dam. 1	H318	Causes serious eye damage.

GHS09 Environment

Aquatic Acute 1H400Very toxic to aquatic life.Aquatic Chronic 1H410Very toxic to aquatic life with long lasting effects.



Acute Tox. 4H302Harmful if swallowed.Skin Sens. 1H317May cause an allergic skin reaction.

Reviewed on 12/05/2017

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

(Contd. of page 1)

- · Label elements
- · GHS label elements The product is classified and labeled according to the Hazard Communication Standard (HCS).
- · Hazard pictograms



· Signal word Danger

Hazard-determining components of labeling:

sulphuric acid 61 %

mercury sulphate

potassium dichromate

Hazard statements

H290 May be corrosive to metals.

- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P310 IF exposed or concerned: Immediately call a poison center/doctor.

· Other hazards

Contact with skin and inhalation of aerosols/ vapours of the preparation should be avoided.

Acid burns have to treated immediately, as it may otherwise cause badly curing wounds.

CAS 7783-35-9: Danger through skin absorption.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** sulfuric acid solution

Composition and Information on Ingredients:

The percent content of the chromium compound mentioned below refers to the amount of the chromate ions dissolved in water. The percent content of the mercury compound mentioned below refers to the amount of the pure mercury therein. Cancer Status IARC: Strong inorganic acid mists containing sulphuric acid can cause cancer.

Percent ranges are used due to the confidential product information.

CAS: 7664-93-9	sulphuric acid	60–70%
EINECS: 231-639-5	🔶 Met. Corr.1, H290; Skin Corr. 1A, H314	
Index number: 016-020-00-8		
RTECS: WS5600000		
CAS: 7783-35-9	mercury sulphate	0.25–1%
EINECS: 231-992-5	Acute Tox. 2, H300; Acute Tox. 1, H310; Acute Tox. 2, H330; STOT RE 2, H373;	
Index number: 080-002-00-6	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
RTECS: OX 0500000		
	(Con	td. on page 3)

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

	(Co	ntd. of page 2)
CAS: 10294-26-5	disilver(1+) sulphate	0.25–1%
EINECS: 233-653-7	♦ Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100)	
CAS: 7778-50-9	potassium dichromate	0.1-0.3%
EINECS: 231-906-6	🚸 Ox. Sol. 2, H272; 🚸 Acute Tox. 3, H301; Acute Tox. 2, H330; 🚯 Resp. Sens. 1,	
Index number: 024-002-00-6	H334; Muta. 1B, H340; Carc. 1B, H350; Repr. 1B, H360; STOT RE 1, H372; 🔶 Skin	
RTECS: HX 7680000	Corr. 1B, H314; 🚯 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; 🍈 Acute Tox. 4,	
	H312; Skin Sens. 1, H317	
· Additional information: For	the wording of the listed hazard phrases refer to section 16.	

4 First-aid measures

· Description of first aid measures · General information: Personal protection for the First Aider. Immediately remove any clothing soiled by the product. · After inhalation: Supply fresh air or oxygen; call for doctor. In case of unconsciousness remove to fresh air, apply artificial respiration, and consult a physician. After skin contact: Wash with polyethylene glycol 400 and then rinse with copious amounts of water. Immediate medical treatment necessary. Failure to treat burns can prevent wounds from healing. After eye contact: Rinse opened eye for several minutes (at least 15 min) under running water. Call a doctor immediately. After swallowing: Rinse out mouth and then drink 1-2 glasses of water. Do not induce vomiting; immediately call for medical help. Most important symptoms and effects, both acute and delayed burns resorption after inhalation: coughing breathing difficulty asthma attacks damage to the affected mucous membranes after swallowing: strong caustic effect metallic taste sickness vomiting bloody diarrhoea pain methaemoglobin formation unconsciousness cramps · Danger: Danger of circulatory collapse. Danger of gastric perforation. Danger of pulmonary edema. Indication of any immediate medical attention and special treatment needed: If swallowed or in case of vomiting, danger of entering the lungs. Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO₂, sand, extinguishing powder.
- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture
- The product is not combustible. Formation of toxic gases is possible during heating or in case of fire.

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

	(Contd. of page 3)
Sulfur oxides (SOx)	
chromium oxides	
Potassium oxide	
Advice for firefighters	
· Protective equipment:	
Wear self-contained respiratory protective device.	
Wear fully protective suit.	
· Additional information	
Collect contaminated fire fighting water separately. It must not enter the sewage system.	
Ambient fire may liberate bazardous vanours	
6 Accidental release measures	
· Personal precautions, protective equipment and emergency procedures	
Advice for non-emergency personnel:	
Wear protective equipment. Keep unprotected persons away.	
Avoid substance contact.	
Ensure adequate ventilation	
Use respiratory protective device against the effects of fumes/dust/aerosol.	
• Advice for emergency responders: Protective equipment: see section 8	
Do not allow product to reach sewage system or any water course	
Inform respective authorities in case of seepage into water course or sewage system.	
· Methods and material for containment and cleaning up:	
Ensure adequate ventilation.	
Use neutralizing agent.	
Neutralize with diluted sodium hydroxide solution.	
Absorb with liquid-binding material (sand, diatomite, universal binders).	
· Poference to other sections	
See Section 8 for information on personal protection equipment	
See Section 13 for disposal information.	
7 Handling and storage	
T Hundning and Storage	
· Handling:	

- · Precautions for safe handling
- Advice on safe handling: Open and handle receptacle with care. Work only in fume cabinet. Prevent formation of aerosols.

· Hygiene measures:

Do not inhale gases / fumes / aerosols. Do not get in eyes, on skin, or on clothing. Take off immediately all contaminated clothing. Store protective clothing separately. Wash hands before breaks and at the end of work. Do not eat, drink or smoke when using this product.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility:
- Store away from metals. Do not store together with alkalis (caustic solutions).
- Store away from flammable substances.
- Further information about storage conditions:
- Store under lock and key and with access restricted to technical experts or their assistants only.
- Store in cool, dry conditions in well sealed receptacles.
- Protect from heat and direct sunlight.
- Protect from exposure to the light.

Protect from humidity and water.

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

This product is hygroscopic. Store in dry conditions.

- Recommended storage temperature: 20°C +/- 5°C (approx. 68°F)
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

	· Control parameters				
	Components with limit values that require monitoring at the workplace:				
	CAS: 7664-93-9 sulphuric acid				
	PEL (USA)	Long-term value: 1 mg/m ³			
	REL (USA)	Long-term value: 1 mg/m ³			
	TLV (USA)	Long-term value: 0.2* mg/m³ *as thoracic fraction			
	EL (Canada	a) Long-term value: 0.2 mg/m³ ACGIH A2; IARC 1			
	EV (Canada	a) Long-term value: 0.2 mg/m³			
	CAS: 7783-	-35-9 mercury sulphate			
	PEL (USA)	Long-term value: 0.1 mg/m³ as Hg; see OSHA standard interpretation memo			
	REL (USA)	Long-term value: 0.05* mg/m³ Ceiling limit value: 0.1 mg/m³ as Hg; *Vapor; Skin			
	TLV (USA)	Long-term value: 0.025 mg/m³ as Hg; Skin; BEI			
	EL (Canada	a) Long-term value: 0.025 mg/m³ as Hg; Skin, R			
	CAS: 10294	4-26-5 disilver(1+) sulphate			
	EL (Canada	a) Short-term value: 0.03 mg/m³ Long-term value: 0.01 mg/m³ as Ag			
	CAS: 7778-	-50-9 potassium dichromate			
	PEL (USA)	Long-term value: 0.005* mg/m³ Ceiling limit value: 0.1** mg/m³ *as Cr(VI) **as CrO3; see 29 CFR 1910.1026			
	REL (USA)	Long-term value: 0.0002 mg/m³ as Cr; See Pocket Guide Apps. A and C			
	TLV (USA)	Short-term value: NIC-0.0005* mg/m³ Long-term value: (0.05) NIC-0.0002* mg/m³ as Cr; *inhalable, BEI, NIC-Skin, DSEN, RSEN			
EL (Canada)		a) Long-term value: 0.025 mg/m ³ Ceiling limit value: 0.1 mg/m ³ as Cr; ACGIH A1, IARC 1			
	- Ingredients	s with biological limit values:			
	CAS: 7783-	-35-9 mercury sulphate			
	BEI (USA)	35 μg/L Medium: urine Time: prior to shift			
Pa		Parameter: Total Inorganic mercury (background)			
		15 μg/L Medium: blood Time: end of shift at end of workweek			
		Parameter: Total inorganic mercury (background)			
			(Contd. on page 6		
_					

(Contd. of page 4)

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

	(Contd. of page
CAS: 7778	8-50-9 potassium dichromate
BEI (USA)) 25 μg/L Medium: urine Time: end of shift at end of workweek Parameter: Total chromium (fume)
	10 μg/L Medium: urine Time: increase during shift Parameter: Total chromium (fume)
· Additiona	al information: The lists that were valid during the creation were used as basis.
· Engineeri Technical See item 7	ing measures: measures and appropriate working operations should be given priority over the use of personal protective equipment. 7.
 Personal Breathing Use respir In case of protective Recomme Protection Acid resist Preventive After use of Material of Butyl rubb Recomme Penetration Value for t The exact Eye prote Tightly sea Face prote 	protective equipment: g equipment: ratory protective device against the effects of fumes/dust/aerosol. brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory device that is independent of circulating air. ended filter device for short term use: Combination filter B-P2 n of hands: tant gloves e skin protection by use of skin-protecting agents is recommended. of gloves apply skin-cleaning agents and skin cosmetics. of gloves ber, BR ended thickness of the material: ≥ 0.3 mm on time of glove material the permeation: Level ≤ 1 (10 min) the the kthrough time has to be found out by the manufacturer of the protective gloves and has to be observed. ection: aled goggles ection
Body pro	tection: Acid resistant protective clothing
In case of protective Recomme Protection Acid resist Preventive After use of Material o Butyl rubb Recomme Penetratio Value for t The exact Eye prote Tightly sea Face prote	brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory edvice that is independent of circulating air. ended filter device for short term use: Combination filter B-P2 n of hands: tant gloves e skin protection by use of skin-protecting agents is recommended. of gloves apply skin-cleaning agents and skin cosmetics. of gloves ber, BR ended thickness of the material: ≥ 0.3 mm on time of glove material the permeation: Level ≤ 1 (10 min) t break through time has to be found out by the manufacturer of the protective gloves and has to be observed. ection: aled goggles ection tection: Acid resistant protective clothing

Limitation and supervision of exposure into the environment:

Avoid release to the environment.

Do not allow product to reach sewage system or any water course.

9 Physical and chemical properties

 Information on basic physical and che Appearance: 	emical properties
Form / Physical state:	Liquid
Color:	Yellow-brown
•••	
· Odor:	Recognizable
Odor threshold:	Not determined.
· pH-value at 20 °C (68 °F):	1
 Melting point/freezing point: 	Not determined.
 Initial boiling point and boiling range: 	> 100 °C (>212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gas):	Not applicable.
· Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not self-igniting.
· Danger of explosion:	Product does not present an explosion hazard.
 Flammability or explosive limits: 	
Lower:	Not applicable.
	(Contd on page 7)

(Contd. on page 7)

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

		(Contd. of page 6)
Upper:	Not applicable.	
· Oxidizing properties:	CAS 7664-93-9 : Oxidizing potential	
 Vapor Pressure: Density at 20 °C (68 °F): Relative density: Vapor density: Evaporation rate: 	Not determined. 1,58 g/cm³ (13.19 lbs/gal) Not determined. Not determined. Not determined.	
[·] Solubility(ies) Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:	Not determined.	
Solvent content: Organic solvents: Water: Solids content:	0,0 % < 20 % < 5 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity see section "Possibility of hazardous reactions"

· Chemical stability Stable at ambient temperature (room temperature).

- Possibility of hazardous reactions
- Corrosive action on metals.

Reacts with metals forming hydrogen (Danger of explosion!)

When diluting, always add acid to water, never vice versa.

Diluting or dissolving in water always causes rapid heating.

Reacts with reducing agents.

Reacts with peroxides.

Reacts with halogenated compounds.

Reacts with oxidizing agents.

Reacts with acids and alkali (lyes).

Reacts with ammonia (NH₃). Conditions to avoid

strong heating

Strong heating (decomposition)

- · Incompatible materials:
- metals

organic substances combustible materials

organic solvents

• Hazardous decomposition products: see section 5

11 Toxicological information

Information on toxicological effects

· Acute tox	· Acute toxicity: Classification according to calculation procedure.			
· Acute tox	icity estimate	e (ATE _(MIX)) - Calculation method:		
Oral	GHS ATE(MIX)	727 mg/kg (.)		
Dermal	GHS ATE(MIX)	933 mg/kg (.)		
Inhalative	GHS ATE(MIX)	7.9 mg/l/4h (aerosol)		
· LD/LC50 values that are relevant for classification:				
CAS: 766	4-93-9 sulphı	uric acid		
Oral	LD50 2	140 mg/kg (rat)		
	(1	UCLID)		

(Contd. on page 8)

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

		(Contd.	of page 7)
	LC 50	510 mg/m³/2h (rat)	
CAC: 770	2 25 0 mar		
CAS: 770	5-35-9 mer		
Orai		57 mg/kg (ATE)	
	LD30.	(RTECS)	
Dermal	LD50	5 mg/kg (ATE)	
	LD50.	625 mg/kg (rat)	
Inhalative	LC50	0.05 mg/l/4h (ATE)	
CAS: 102	94-26-5 dis	silver(1+) sulphate	
Oral	LD50	>5000 mg/kg (rat) (OECD 401) (Registrant, ECHA)	
CAS: 777	8-50-9 pot	assium dichromate	
Oral	LD50	90.5 mg/kg (rat) (OECD 401)	
		(ECHA, registrant: LD50 = 90.5 mg/kg female to 168.0 mg/kg male)	
	LDLo	26 mg/kg (child)	
		143 mg/kg (man)	
Dermal	LD50	1170 mg/kg (rat) (IUCLID)	
Inhalative	LC50	0.094 mg/l/4h (rat) (OECD 403, Aerosol)	
	LD50 IPR	28 mg/kg (rat)	
• Primary in • on the ski • on the eye Causes se Risk of blin	ritant effe in: Causes e: erious eye o ndness!	act: s severe skin burns. damage.	
		iponents.	
Irritation of	f skin	CD 404 (rabbit: no irritation)	
Irritation o	f eves OF	CD 405 (rabbit: hurns)	
CAS: 777	8-50-9 not	assium dichromate	
Irritation o	f skin OF	CD 404 (rabbit: irritation)	
 Sensitizat May cause May cause 	tion: e allergy or e an allergi	asthma symptoms or breathing difficulties if inhaled. c skin reaction.	
· Informatio	on on com	iponents:	
CAS: 777	8-50-9 pot	assium dichromate	
Sensitizati	on Patch t	test (human) (positive) (IUCLID)	
	enic cated	ories	
· IARC (Inte	ernational	Agency for Research on Cancer)	
CAS: 7664	1-93-9 sul	phuric acid	1
CAS: 7783	3-35-9 me	rcury sulphate	3
CAS: 7778	3-50-9 pot	assium dichromate	1
· NTP (Nati	onal Toxic	cology Program)	
CAS: 7664	1-93-9 sult	phuric acid	ĸ
CAS: 7778	3-50-9 pot	assium dichromate	K
	(Occupati	ional Safety & Health Administration)	
None of th		nte is listed	
· Other infe	rmation		
see sectio Cancer St mists cont	n 8 / 15 atus of Sul aining sulfu	furic acid: The International Agency for Research on Cancer (IARC) has classified "strong inorganic uric acid" as a known human carcinogen, (IARC category 1). This classification applies only to mists	acid

containing sulfuric acid and not to sulfuric acid or sulfuric acid solutions. A2 (Suspected for humans) by ACGIH

Printing date 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

Reviewed on 12/05/2017

(Contd. of page 8)

• **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction):** The following statements refer to the mixture:

Muta. 1B, Carc. 1B, Repr. 1B

· Synergistic Products: None

- · Germ cell mutagenicity May cause genetic defects.
- · Carcinogenicity May cause cancer.
- Reproductive toxicity May damage fertility or the unborn child.
- · STOT (specific target organ toxicity) -single exposure Based on available data, the classification criteria are not met.
- STOT (specific target organ toxicity) -repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Mercury compounds have a cytotoxic and protoplasmatoxic effect.

- The principal signs manifest themselves in the CNS.
- Inhalable chromium (VI) compounds have clearly shown themselves to be carcinogenic in animal experiments.

Poor tendency for ulcers to heal following penetration of substance into the wound.

Lethal dose (man): 0.5 g

Antidotes: chelating agents such as EDTA, DMPS

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach. The aerosol is corrosive to the eyes, the skin and the respiratory tract. Inhalation of aerosols may cause lung oedema. Sulfuric acid: erosion of the teeth, cancer

• Experience with humans:

CAS 7778-50-9: Can cause liver damage.

CAS 7778-50-9: Can cause kidney damages.

- CAS 7778-50-9: May cause lung damages.
- CAS 7778-50-9: Can cause cardiac damages.
- CAS 1110-50-9. Can cause cardiac damages

12 Ecological information

· Toxicit	· Toxicity				
· Aquati	· Aquatic toxicity:				
CAS: 7	664-93-9 sulphuric acid				
EC50	>100 mg/l/48h (Daphnia magna) (OECD 202)				
1.050					
LC50	(Merck)				
CAS: 7	783-35-9 mercury sulphate				
LC50	0.5 mg/l/48h (gold orfe)				
EC50	0.005–3.6 mg/l/48h (Daphnia magna)				
LC50	0.19 mg/l/96h (fathhead minnow)				
CAS: 1	0294-26-5 disilver(1+) sulphate				
EC50	0.0045 mg/l/48h (Daphnia magna) (GESTIS)				
EC50	0.0049 mg/l/96h (fathhead minnow)				
EC10	0.00214 mg/l (Daphnia magna) (ASTM) (21d, test substance: AgNO₃)				
	0.00039 mg/l (fathhead minnow) (ASTM E1241-98) (28d, test substance: AgNO₃, result in mg/l Ag)				
CAS: 7	778-50-9 potassium dichromate				
EC50	0.62 mg/l/48h (Daphnia magna) (OECD 202) (Merck)				
NOEC	0.016–0.064 mg/l (Daphnia magna) (7d)				
	6 mg/l (fathhead minnow) (7d)				
IC50	0.16–0.59 mg/l/96 h (Chlorella vulgaris) (IUCLID)				
EC50	0.31 mg/l/72 h (Desmodesmus subspicatus)				
LC50	58.5 mg/l/96h (byr)				
	(Contd. on page 10)				

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

	(Contd. of page 9)
0.131 mg/l/96h (bluegill)	
160 mg/l/96h (guppy)	
26.13 mg/l/96h (fathhead minnow)	
(Merck/IUCLID)	
· Bacterial toxicity:	
CAS: 7778-50-9 potassium dichromate	
EC50 58 mg/l (Photobacterium phosphoreum) (30 min; Microtox-Test)	
Other information:	
Toxic for fish:	
sulfates > 7 g/l	
Persistence and degradability No further relevant information available.	
Other information:	
Mixture of inorganic compounds.	
Methods for the determination of biodegradability are not applicable to inorganic substances.	
Bioaccumulative potential	
BCF = Bioconcentration factor	
CAS: 10294-26-5 disilver(1+) sulphate	
BCF 2.5 (rainbow trout)	
(8d, 15°C, test substance: AgNO₃)	
CAS: 7778-50-9 potassium dichromate	
BCF 17.4 (rainbow trout)	
Mobility in soil No further relevant information available.	
· Other adverse effects	
Forms corrosive mixtures with water even if diluted.	
Harmful effect due to pH shift.	
Avoid transfer into the environment.	

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Hand over to hazardous waste disposers.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN2922
· UN proper shipping name	
DOT	Corrosive liquids, toxic, n.o.s. (Sulfuric acid, Mercury sulfates)
· IMDG	CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE), MARINE POLLUTANT
ΙΑΤΑ	CORROSIVE LIQUID, TOXIC, N.O.S. (SULPHURIC ACID, MERCURY SULPHATE)
· Transport hazard class(es)	
· DOT	
CORROSIVE 6 6	
· Class	8 Corrosive substances

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

	(Contd. of page 10)
· Label	8, 6.1
·IMDG	
· Class · Label	8 Corrosive substances 8/6.1
·IATA	
· Class · Label	8 Corrosive substances 8 (6.1)
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: mercury sulphate
· Marine pollutant:	Yes Symbol (fish and tree)
 Special precautions for user 	Warning: Corrosive substances
· Danger code (Kemler):	86 E A S B
· Segregation groups	F-A,S-D Acids, heavy metals and their salts (including their organometallic
	compounds)
· Stowage Category	B
· Stowage Code	SW2 Clear of living quarters.
 Transport in bulk according to Annex II of MARPOL73/7 and the IBC Code 	78 Natawijasha
	Not applicable.
[•] Transport/Additional information:	
DOT	
· Quantity limitations	On passenger aircraft/rail: 1 L On cargo aircraft only: 30 l
· Limited quantity (LQ):	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
·IMDG	
Limited quantities (LQ)	1L Code: E2
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara
 Section 355 (Extremely hazardous substances):

CAS: 7664-93-9 sulphuric acid

CAS: 7783-35-9 mercury sulphate

Section 313 (Specific toxic chemical listings):

This mixture contains Chromic acid, dipotassium salt [listed as **undefined** - Cr(VI)] which is subject to the reporting requirements of Section 313 SARA Title III and 40 CFR Part 372.

CAS: 7664-93-9 sulphuric acid

Printing date 12/05/2017

Reviewed on 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

		Contd. of page 11)
CAS: 7783-35-9 mercury sulphate		
CAS: 10294-26-5 disilver(1+) sulphate		
CAS: 7778-50-9 potassium dichromate		
• TSCA (Toxic Substances Control Act):		
All ingredients are listed.		
 Proposition 65 Chemicals known to cause cancer: Chromium (hexavalent) compounds are listed in California Proposition 65 as carcinogens. 		
CAS: 7778-50-9 potassium dichromate		
Chemicals known to cause reproductive toxicity for females: Chemium (hovevelont) compounds are listed in Colifernia Drangeition 65 on toxic to reproduct	ation for formalian	
CAS: 7778.50.9 potassium dichromate	cuon for lemales.	
CAS. 1118-50-9 polassium dichromate		
Chromium (hexavalent) compounds are listed in California Proposition 65 as toxic to reprodu	ction for males.	
CAS: 7778-50-9 potassium dichromate		
Chemicals known to cause developmental toxicity:		
Chromium (hexavalent) compounds are listed in California Proposition 65 as toxic to develop	ement.	
CAS: 7783-35-9 mercury sulphate		
CAS: 7778-50-9 potassium dichromate		
· New Jersey Right-to-Know List:		
CAS: 7664-93-9 sulphuric acid		
CAS: 7783-35-9 mercury sulphate		
CAS: 7778-50-9 potassium dichromate		
· New Jersey Special Hazardous Substance List:		
CAS: 7664-93-9 sulphuric acid		CA, CO, R2
CAS: 7778-50-9 potassium dichromate		CA, MU
· Pennsylvania Right-to-Know List:		-
CAS: 7664-93-9 sulphuric acid		
CAS: 7783-35-9 mercury sulphate		
CAS: 7778-50-9 potassium dichromate		
· Pennsylvania Special Hazardous Substance List:		
CAS: 7664-93-9 sulphuric acid		E
CAS: 7783-35-9 mercury sulphate		E
CAS: 7778-50-9 potassium dichromate		E
· EPA (Environmental Protection Agency)		
CAS: 7783-35-9 mercury sulphate	D	
CAS: 7778-50-9 potassium dichromate	A(inh), D(oral), K/L(ir	h), CBD(oral)
NIOSH-Ca (National Institute for Occupational Safety and Health) Chromium, hexavalent [Cr(VI)]		
CAS: 7778-50-9 potassium dichromate		

Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning young persons must be observed.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H272 May intensify fire; oxidizer. H290 May be corrosive to metals. H300 Fatal if swallowed.

H301 Toxic if swallowed.

Printing date 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

(Contd. of page 12) H310 Fatal in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H330 Fatal if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H340 May cause genetic defects. H350 May cause cancer. H360 May damage fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. Date of preparation / last revision 12/05/2017 / 45 Abbreviations and acronyms: EC50: effective concentration, 50 percent (in vivo) OECD: Organisation for Economic Co-operation and Development STOT: specific target organ toxicity SE: single exposure RE: repeated exposure EC50: half maximal effective concentration IC50: hallf maximal inhibitory concentration NOEL or NOEC: No Observed Effect Level or Concentration ACGIH[®] - American Conference of Governmental Industrial Hygienists •A1 - Confirmed human carcinogen •A2 - Suspected human carcinogen •A3 - Confirmed animal carcinogen with unknown relevance to humans •A4 - Not classifiable as a human carcinogen •A5 - Not suspected as a human carcinogen IARC - International Agency for Research on Cancer •Group 1 - Carcinogenic to humans •Group 2A - Probably carcinogenic to humans •Group 2B - Possibly carcinogenic to humans •Group 3 - Not classifiable as to carcinogenicity to humans •Group 4 - Probably not carcinogenic to humans NTP - National Toxicology Program, U.S. Department of Health and Human Services •Group K - Known to be Human Carcinogens •Group R - Reasonably Anticipated to be Human Carcinogens ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Ox. Sol. 2: Oxidizing solids - Category 2 Met. Corr.1: Corrosive to metals - Category 1 Acute Tox. 2: Acute toxicity – Category 2 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 1: Acute toxicity – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 1B: Germ cell mutagenicity – Category 1B Carc. 1B: Carcinogenicity – Category 1B Repr. 1B: Reproductive toxicity – Category 1B STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

· Sources

Data arise from safety data sheets, reference works and literature. ECHA: European CHemicals Agency http://echa.europa.eu Reviewed on 12/05/2017

Printing date 12/05/2017

Trade name: COD / CSB 0-15000 mg/l

IUCLID (International Uniform Chemical Information Database) GESTIS- Stoffdatenbank (Substance Database, Germany) RTECS (Registry of Toxic Effects of Chemical Substances) International Chemical Safety Cards (ICSCs)

 \cdot * Data compared to the previous version altered.

Reviewed on 12/05/2017

(Contd. of page 13)

US —