

Centrifuge NEYA 16R REFRIGERATED HIGH SPEED , 4x175 ml, 16000 rpm, 10 P rograms



Item Code: 40100342

DATA SHEET

Features

Power supply	220 ± 10% - 50 Hz V
Entrance height	275 mm
Capacity max. (fixed angle rotor)	6 x 100 ml
Capacity max. (swing rotor)	4 x 175 ml
Consumption	750 W
Imbalance control	Yes
Time and date	Yes
Dimension	730 x 640 x 330 mm
Dimensions height when open	670 mm
Standard - directives	2014/35/EU ; 2014/30/EU ; 2015/863 ; 2006/42/EC ; IEC61010-1:2010+A1:2016 ; IEC61010-2-020:2016 ; IEC61326-1:2012 ; IEC61010-2-120:2016 ; EN378-1 ; EN378-2
RCF display	Yes
Display temperature	Yes
Precooling function	Yes
Spin function	Yes
Warranty	2 anni
RCF setting	Yes
RPM settings	Yes
Temperature settings	Yes
Rotor indication	Yes
Speed limiter	Yes
Max Ampere	4 A
Name	Neya 16 R
Weight	70 kg
Weight (with packaging, no rotor)	92 kg
Programs	Yes
Acceleration ramps	0 ÷ 9 (0 = min. - 9 = max.)
Deceleration ramps	0 ÷ 9 (0 = no brake, 1 = min. - 9 = max.)
RCF max (fixed angle rotor)	21000 x g

RCF max (swing rotor)	3600 x g
RCF max	21000 xg
Coolant quantity	45 g
Coolant type	R290 CFC-free
Noise	55 dB
Control system	Yes
Timer	00:30 ÷ 99:50 (mm:ss) e in continuo hh:mm
Type of motor	Brushless induction
Maximum speed with swing rotor	4500 rpm
maximum speed	16000 rpm
Max speed check	Yes

DS_40100342_rev. _06-09-2023